

OB1 PlumbersPal Hybrid Sealant & Adhesive White  
Date: 04.08.2023

Replaces: N/A  
Ref: 0520.0.BB/DL

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product Name OB1 PlumbersPal Hybrid Sealant & Adhesive White  
Pure substance/mixture Mixture

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Adhesives and/or sealants  
Uses advised against None known

### 1.3. Details of the supplier of the safety data sheet

#### Company Name

Siroflex Limited  
Dodworth Business Park  
Dodworth, Barnsley  
South Yorkshire, S75 3SP  
Tel +44 (0)1226 771600 Fax +44 (0)1226 771601  
Further information available from: [www.ob1original.com](http://www.ob1original.com)

### 1.4. Emergency telephone number

United Kingdom + 44 (0) 1226 771600 (Office Hours Only)  
Ireland **NPIC - National Poison Information Centre**  
Members of the Public: +353 (01) 8092166 (8.00 am to 10.00 pm - 7 days a week)  
Europe Healthcare Professionals: +353 (01) 8092566 (24 hour service)  
112

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

### 2.2. Label elements

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

Signal word  
None

### Hazard statements

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

### EU Specific Hazard Statements

EUH208 - Contains Trimethoxyvinylsilane. May produce an allergic reaction  
EUH210 - Safety data sheet available on request

### 2.3. Other hazards

# SAFETY DATA SHEET

OB1 PlumbersPal Hybrid Sealant & Adhesive White  
Date: 04.08.2023

Replaces: N/A  
Ref: 0520.0.BB/DL

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing. Causes mild skin irritation.

## PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

Not applicable

### 3.2 Mixtures

Chemical name	EC No (EU Index No)	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH registration number
Trimethoxyvinylsilane	(014-049-00-0) 220-449-8	2768-02-7	1 - <3	Skin Sens. 1B (H317) Acute Tox. 4 (H332) Flam. Liq. 3 (H226)	-	01-2119513215-52-XXXX
Fatty acids, C16-18, sodium salts	270-299-2	68424-38-4	1 - <2.5	Aquatic Chronic 3 (H412)	-	01-2119648083-41-xxxx
1-Propanamine, 3-(trimethoxysilyl)-	237-511-5	13822-56-5	1 - <2.5	Skin Irrit. 2 (H315) Eye Dam. 1 (H318)	-	01-2119510159-45-XXXX
Titanium dioxide	(022-006-00-2) 236-675-5	13463-67-7	0.1- <1	[C]	-	01-2119489379-17-XXXX
Diocetyl tin oxide	212-791-1	870-08-6	0.1 - <0.5	STOT SE 2 (H371)	-	01-2119971268-27-xxxx

### Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

<b>General advice</b>	Show this safety data sheet to the doctor in attendance. If medical advice is needed, have product container or label at hand.
<b>Inhalation</b>	Remove to fresh air. If symptoms persist, call a doctor.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

# SAFETY DATA SHEET

OB1 PlumbersPal Hybrid Sealant & Adhesive White  
Date: 04.08.2023

Replaces: N/A  
Ref: 0520.0.BB/DL

---

	Remove contact lenses, if present and easy to do. Continue rinsing.
<b>Skin contact</b>	In the case of skin irritation or allergic reactions see a doctor. Wash skin with soap and water.
<b>Ingestion</b>	Call a doctor immediately. Rinse mouth thoroughly with water. Never give anything by mouth to an unconscious person. Small amounts of toxic methanol are released by hydrolysis.

#### **4.2. Most important symptoms and effects, both acute and delayed**

**Symptoms** None known.

#### **4.3. Indication of any immediate medical attention and special treatment needed**

**Note to doctors** Treat symptomatically. Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing.

### **SECTION 5: Firefighting measures**

#### **5.1. Extinguishing media**

**Suitable Extinguishing Media** Water spray, carbon dioxide (CO<sub>2</sub>), dry chemical, alcohol-resistant foam.

**Unsuitable extinguishing media** Full water jet.

#### **5.2. Special hazards arising from the substance or mixture**

**Specific hazards arising from the chemical** Thermal decomposition can lead to release of irritating gases and vapours.

**Hazardous combustion products** Carbon oxides. Carbon monoxide. Carbon dioxide (CO<sub>2</sub>). Nitrogen oxides (NO<sub>x</sub>). Silicon oxides. Silicon dioxide.

#### **5.3. Advice for firefighters**

**Special protective equipment and precautions for fire-fighters** Wear self contained breathing apparatus for fire fighting if necessary.

### **SECTION 6: Accidental release measures**

#### **6.1. Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Use personal protective equipment as required. Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing.

**For emergency responders** Use personal protection recommended in Section 8.

#### **6.2. Environmental precautions**

**Environmental precautions** Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section 12 for additional Ecological Information.

#### **6.3. Methods and material for containment and cleaning up**

**Methods for containment** Do not scatter spilled material with high pressure water streams.

**Methods for cleaning up** Take up mechanically, placing in appropriate containers for disposal.

**Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

# SAFETY DATA SHEET

OB1 PlumbersPal Hybrid Sealant & Adhesive White  
Date: 04.08.2023

Replaces: N/A  
Ref: 0520.0.BB/DL

## 6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

**Advice on safe handling** Ensure adequate ventilation.

**General hygiene considerations** Do not eat, drink or smoke when using this product. Wash hands before breaks and after work.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage Conditions** Protect from moisture. Keep away from food, drink and animal feedingstuffs.

**Recommended storage temperature** Keep at temperatures between 10 and 35 °C.

### 7.3. Specific end use(s)

**Specific use(s)**  
Adhesives and/or sealants.

**Risk Management Methods (RMM)** The information required is contained in this Safety Data Sheet.

**Other information** Observe technical data sheet.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

**Exposure Limits** Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product

Chemical name	European Union	United Kingdom
Methyl alcohol 67-56-1	TWA: 200 ppm TWA: 260 mg/m <sup>3</sup> *	TWA: 200 ppm TWA: 266 mg/m <sup>3</sup> STEL: 250 ppm STEL: 333 mg/m <sup>3</sup> Sk*
Titanium dioxide 13463-67-7	-	TWA: 10 mg/m <sup>3</sup> TWA: 4 mg/m <sup>3</sup> STEL: 30 mg/m <sup>3</sup> STEL: 12 mg/m <sup>3</sup>
Diocetyl tin oxide 870-08-6	-	TWA: 0.1 mg/m <sup>3</sup> STEL: 0.2 mg/m <sup>3</sup> Sk*

Chemical name	European Union	Ireland	United Kingdom
Methyl alcohol 67-56-1	-	15 mg/L (urine - Methanol end of shift)	-

**Derived No Effect Level (DNEL)** No information available

### Derived No Effect Level (DNEL)

#### Trimethoxyvinylsilane (2768-02-7)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker	Inhalation	27,6 mg/m <sup>3</sup>	

# SAFETY DATA SHEET

OB1 PlumbersPal Hybrid Sealant & Adhesive White  
Date: 04.08.2023

Replaces: N/A  
Ref: 0520.0.BB/DL

Systemic health effects Long term worker	Dermal	3,9 mg/kg bw/d	
Systemic health effects Long term			

<b>1-Propanamine, 3-(trimethoxysilyl)- (13822-56-5)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	58 mg/m <sup>3</sup>	
worker Long term	Dermal	8.3 mg/kg bw/d	
Short term worker	Inhalation	58 mg/m <sup>3</sup>	
Short term worker	Dermal	8.3 mg/kg bw/d	

<b>Titanium dioxide (13463-67-7)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Local health effects	Inhalation	10 mg/m <sup>3</sup>	

<b>Diocetyl tin oxide (870-08-6)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Dermal	0.05 mg/kg bw/d	
worker Long term Systemic health effects	Inhalation	0.004 mg/m <sup>3</sup>	

<b>Derived No Effect Level (DNEL)</b>			
<b>Trimethoxyvinylsilane (2768-02-7)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Systemic health effects Long term	Inhalation	18,9 mg/m <sup>3</sup>	
Consumer Systemic health effects Long term	Dermal	7,8 mg/kg bw/d	
Consumer Systemic health effects Long term	Oral	0,3 mg/kg bw/d	

<b>Titanium dioxide (13463-67-7)</b>			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Oral	700 mg/kg bw/d	

<b>Diocetyl tin oxide (870-08-6)</b>			
Type	Exposure route	Derived No Effect Level	Safety factor

# SAFETY DATA SHEET

OB1 PlumbersPal Hybrid Sealant & Adhesive White  
Date: 04.08.2023

Replaces: N/A  
Ref: 0520.0.BB/DL

		(DNEL)	
Consumer Long term Systemic health effects	Oral	0.0005 mg/kg bw/d	
Consumer Long term Systemic health effects	Dermal	0.025 mg/kg bw/d	
Consumer Long term Systemic health effects	Inhalation	0.0009 mg/m <sup>3</sup>	

## Predicted No Effect Concentration (PNEC)

Predicted No Effect Concentration (PNEC)	
Trimethoxyvinylsilane (2768-02-7)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.34 mg/l
Marine water	0.034 mg/l
Microorganisms in sewage treatment	110 mg/l

1-Propanamine, 3-(trimethoxysilyl)- (13822-56-5)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.33 mg/l
Microorganisms in sewage treatment	13 mg/l
Soil	0.04 mg/l
Marine water	0.033 mg/l

Titanium dioxide (13463-67-7)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Marine water	0.0184 mg/l
Freshwater sediment	1000 mg/kg
Freshwater	0.184 mg/l
Marine sediment	100 mg/kg
Soil	100 mg/kg
Microorganisms in sewage treatment	100 mg/l
Freshwater - intermittent	0.193 mg/l

Diocetyl tin oxide (870-08-6)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater sediment	0.02798 mg/kg dry weight
Marine sediment	0.002798 mg/kg dry weight
Microorganisms in sewage treatment	100 mg/l

## 8.2. Exposure controls

**Engineering controls**                      Ensure adequate ventilation, especially in confined areas.

### Personal protective equipment

- Eye/face protection**                      Wear safety glasses with side shields (or goggles). Eye protection must conform to standard EN 166.
- Hand protection**                              Wear suitable gloves. Recommended Use: Neoprene™. Nitrile rubber. Butyl rubber. Glove thickness > 0.7mm. The breakthrough time for the mentioned glove material is in general greater than 480 min. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. Gloves must conform to standard EN 374
- Skin and body protection**                      None under normal use conditions.
- Respiratory protection**                      In case of inadequate ventilation wear respiratory protection. Wear a respirator conforming to EN 140 with Type A/P2 filter or better. Ensure adequate ventilation, especially in confined areas.
- Recommended filter type:**                      Organic gases and vapours filter conforming to EN 14387. White. Brown.

# SAFETY DATA SHEET

OB1 PlumbersPal Hybrid Sealant & Adhesive White  
Date: 04.08.2023

Replaces: N/A  
Ref: 0520.0.BB/DL

**Environmental exposure controls** Do not allow uncontrolled discharge of product into the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	Solid
Appearance	Paste
Colour	See section 1 for more information
Odour	Characteristic.
Odour threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
Melting point / freezing point	No data available	None known
Initial boiling point and boiling range	No data available	None known
Flammability	No data available	None known
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Flash point	> 60 °C	
Autoignition temperature	No data available	None known
Decomposition temperature		None known
pH	.	
pH (as aqueous solution)	No data available	None known
Kinematic viscosity	> 21 mm <sup>2</sup> /s	
Dynamic viscosity	No data available	
Water solubility	No data available. Product cures with moisture	
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Vapour pressure	No data available	None known
Relative density	No data available	None known
Bulk Density	No data available	
Density	1.50	
Relative vapour density	No data available	None known
Particle characteristics		
Particle Size	No information available	
Particle Size Distribution	No information available	

### 9.2. Other information

Solid content (%)	No information available
VOC content	No data available

9.2.1. Information with regards to physical hazard classes  
Not applicable

9.2.2. Other safety characteristics  
No information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity** Product cures with moisture.

### 10.2. Chemical stability

# SAFETY DATA SHEET

OB1 PlumbersPal Hybrid Sealant & Adhesive White  
Date: 04.08.2023

Replaces: N/A  
Ref: 0520.0.BB/DL

**Stability** Stable under normal conditions.

## Explosion data

**Sensitivity to mechanical impact** None.

**Sensitivity to static discharge** None.

## 10.3. Possibility of hazardous reactions

**Possibility of hazardous reactions** None under normal processing.

## 10.4. Conditions to avoid

**Conditions to avoid** Product cures with moisture. Protect from moisture. Exposure to air or moisture over prolonged periods. Do not freeze. Keep away from open flames, hot surfaces and sources of ignition.

## 10.5. Incompatible materials

**Incompatible materials** None known based on information supplied.

## 10.6. Hazardous decomposition products

**Hazardous decomposition products** Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Information on likely routes of exposure

#### Product Information

**Inhalation** Based on available data, the classification criteria are not met.

**Eye contact** Based on available data, the classification criteria are not met.

**Skin contact** Based on available data, the classification criteria are not met. Causes mild skin irritation. May cause sensitisation in susceptible persons.

**Ingestion** Based on available data, the classification criteria are not met.

#### Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** Prolonged contact may cause redness and irritation.

#### Acute toxicity

#### Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (inhalation-vapour) 625.50 mg/l

#### Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Trimethoxyvinylsilane	LD50 = 7120 -7236 mg/kg (Rattus) OECD 401	= 3540 mg/kg (Oryctolagus cuniculus)	LC50 (4hr) 16.8 mg/l (Rattus) OECD TG 403



# SAFETY DATA SHEET

OB1 PlumbersPal Hybrid Sealant & Adhesive White  
Date: 04.08.2023

Replaces: N/A  
Ref: 0520.0.BB/DL

Fatty acids, C16-18, sodium salts	>5000 mg/kg (Rattus)(OECD 401)	> 2 mL/kg (Oryctolagus cuniculus)	-
1-Propanamine, 3-(trimethoxysilyl)-	LD50 (Rattus) > 2000 mg/ kg (2,97 ml/kg) (OECD 401)	LD50 (Oryctolagus cuniculus) > 2000 mg/kg 11,3 ml/kg OECD 402	-
Titanium dioxide	>10000 mg/kg (Rattus)	LD50 > 5000 mg/Kg	= 5.09 mg/L ( Rattus ) 4 h
Diocetyl tin oxide	=2500 mg/kg (Rattus)	LD50 > 2000 mg/kg (Rattus) OECD 402	-

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Skin corrosion/irritation** Classification based on data available for ingredients. May cause skin irritation.

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
	Rabbit	Dermal	0.5 mL	24 hours	Non-irritant

Titanium dioxide (13463-67-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion	Rabbit	Dermal			Non-irritant

**Serious eye damage/eye irritation** No classification is proposed, based on conclusive negative data. By analogy to another tested similar product: No irritation after contact to the eyes. (H319 is void).

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD 437 Bovine Corneal Opacity and Permeability (BCOP) test	Bovine	Corneal	Product 100 %	10 minutes	Product score <3 Non-irritant

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	eye		24 hours	Non-irritant

1-Propanamine, 3-(trimethoxysilyl)- (13822-56-5)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	eye		72 hours	irritant

Titanium dioxide (13463-67-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405: Acute Eye Irritation/Corrosion	Rabbit	Eye			Non-irritant

**Respiratory or skin sensitisation** OECD Test No. 406: Skin Sensitisation. No sensitisation responses were observed. No classification is proposed, based on conclusive negative data. May cause sensitisation in susceptible persons.

Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation	Guinea pig	Dermal	No sensitisation responses were observed

Trimethoxyvinylsilane (2768-02-7)

# SAFETY DATA SHEET

OB1 PlumbersPal Hybrid Sealant & Adhesive White  
Date: 04.08.2023

Replaces: N/A  
Ref: 0520.0.BB/DL

Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation, Buehler test	Guinea pig	Dermal	sensitising

1-Propanamine, 3-(trimethoxysilyl)- (13822-56-5)

Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation	Guinea pig	Dermal	Did not cause sensitisation on laboratory animals

Titanium dioxide (13463-67-7)

Method	Species	Exposure route	Results
OECD Test No. 406: Skin Sensitisation	Guinea pig	Dermal	Not a skin sensitiser
OECD Test No. 429: Skin Sensitisation: Local Lymph Node Assay	Mouse	Dermal	Not a skin sensitiser

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

Component Information  
Trimethoxyvinylsilane (2768-02-7)

Method	Species	Results
OECD Test No. 471: Bacterial Reverse Mutation Test	in vitro	Not mutagenic

**Carcinogenicity** Based on available data, the classification criteria are not met.

**Reproductive toxicity** Based on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Results
OECD Test No. 422: Combined Repeated Dose Toxicity Study with the Reproduction/Developmental Toxicity Screening Test	Rat	Not Classifiable

1-Propanamine, 3-(trimethoxysilyl)- (13822-56-5)

Method	Species	Results
OECD Test No. 408: Repeated Dose 90-Day Oral Toxicity Study in Rodents	Rat	Not Classifiable

**STOT - single exposure** Based on available data, the classification criteria are not met.

Diocetyl tin oxide (870-08-6)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 422: Combined Repeated Dose Toxicity Study with the Reproduction/Developmental Toxicity Screening Test	Rat	Oral	5 mg/kg	28 days	0.3 - 0.5 mg/kg bw/d May cause damage to the following organs: Immune system

**STOT - repeated exposure** Based on available data, the classification criteria are not met.

# SAFETY DATA SHEET

OB1 PlumbersPal Hybrid Sealant & Adhesive White  
Date: 04.08.2023

Replaces: N/A  
Ref: 0520.0.BB/DL

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 413: Sub-chronic Inhalation Toxicity: 90-day Study	Rat	Inhalation vapour		90 days	0.058 NOAEL

Diocetyl tin oxide (870-08-6)

Method	Species	Exposure route	Effective dose	Exposure time	Results
	Rat Rabbit			28 days	0.3 -0.5 mg/kg bw/d

**Aspiration hazard** Based on available data, the classification criteria are not met.

## 11.2. Information on other hazards

### 11.2.1. Endocrine disrupting properties

**Endocrine disrupting properties** No information available.

### 11.2.2. Other information

**Other adverse effects** No information available.

## SECTION 12: Ecological information

### 12.1. Toxicity

#### Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Trimethoxyvinylsilane 2768-02-7	EC 50 (72h) > 957 mg/l (Desmodesmus subspicatus) EU Method C.3	LC50 (96h) = 191 mg/l (Oncorhynchus mykiss)	-	EC50(48hr) 168.7mg/l (Daphnia magna)		
Fatty acids, C16-18, sodium salts 68424-38-4	EC50: =120mg/L (96h, Desmodesmus subspicatus)	-	-	EC50: =86mg/L (72h, Gammarus pulex)		
1-Propanamine, 3-(trimethoxysilyl)- 13822-56-5	EC50 (72h) > 1000 mg/l (Desmodesmus subspicatus) EU Method C.3 (Algal Inhibition test)	LC50 (96h) > >934 mg/L (Danio rerio) OECD 203	-	EC50 (48h) = 331 mg/L (Daphnia magna) OECD 202		
Titanium dioxide 13463-67-7	LC50 (96h) >10000 mg/l (Cyprinodon variegatus) OECD 203	-	-	-		
Diocetyl tin oxide 870-08-6	EC50 (3hr) >1.000 mg/l (bacteria) (Activated Sludge, Respiration Inhibition Test)	LC50 (96hr) >0,09 mg/l (Brachydanio rerio (zebra)) (Acute Toxicity Test)	-	EC50 (48Hr) >0,21 mg/l (Daphnia magna (Dappnia magna)) (Daphnia sp. Acute Immobilisation)		

# SAFETY DATA SHEET

OB1 PlumbersPal Hybrid Sealant & Adhesive White  
Date: 04.08.2023

Replaces: N/A  
Ref: 0520.0.BB/DL

				Test)		
--	--	--	--	-------	--	--

## 12.2. Persistence and degradability

**Persistence and degradability** No information available.

Trimethoxyvinylsilane (2768-02-7)

Method	Exposure time	Value	Results
OECD Test No. 301F: Ready Biodegradability: Manometric Respirometry Test (TG 301 F)	28 days	BOD	51 % Not readily biodegradable

1-Propanamine, 3-(trimethoxysilyl)- (13822-56-5)

Method	Exposure time	Value	Results
OECD Test No. 301A: Ready Biodegradability: DOC Die-Away Test (TG 301 A)	28 days		67 % Not readily biodegradable

Diocetyl tin oxide (870-08-6)

Method	Exposure time	Value	Results
OECD Test No. 301F: Ready Biodegradability: Manometric Respirometry Test (TG 301 F)	755 hours	biodegradation	Not readily biodegradable 2 %

## 12.3. Bioaccumulative potential

**Bioaccumulation**

### Component Information

Chemical name	Partition coefficient
Trimethoxyvinylsilane	1.1
Fatty acids, C16-18, sodium salts	3.3
Diocetyl tin oxide	6

## 12.4. Mobility in soil

**Mobility in soil** No information available.

## 12.5. Results of PBT and vPvB assessment

**PBT and vPvB assessment** No information available.

Chemical name	PBT and vPvB assessment
Trimethoxyvinylsilane	The substance is not PBT / vPvB
Fatty acids, C16-18, sodium salts	The substance is not PBT / vPvB
1-Propanamine, 3-(trimethoxysilyl)-	The substance is not PBT / vPvB
Titanium dioxide	The substance is not PBT / vPvB PBT assessment does not apply
Diocetyl tin oxide	The substance is not PBT / vPvB

## 12.6. Endocrine disrupting properties

**Endocrine disrupting properties** No information available.

## 12.7. Other adverse effects

No information available.

# SAFETY DATA SHEET

OB1 PlumbersPal Hybrid Sealant & Adhesive White  
Date: 04.08.2023

Replaces: N/A  
Ref: 0520.0.BB/DL

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

<b>Waste from residues/unused products</b>	Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable.
<b>Contaminated packaging</b>	Handle contaminated packages in the same way as the product itself.
<b>European Waste Catalogue</b>	08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09
<b>Other information</b>	Waste codes should be assigned by the user based on the application for which the product was used.

## SECTION 14: Transport information

### Land transport (ADR/RID)

14.1 UN number or ID number	Not regulated
14.2 Proper Shipping Name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special Provisions	None

### IMDG

14.1 UN number or ID number	Not regulated
14.2 Proper Shipping Name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Marine pollutant	NP
14.6 Special Provisions	None
14.7 Maritime transport in bulk according to IMO instruments	Not applicable

### Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number	Not regulated
14.2 Proper Shipping Name	Not regulated
14.3 Transport hazard class(es)	Not regulated
14.4 Packing group	Not regulated
14.5 Environmental hazards	Not applicable
14.6 Special Provisions	None

## Section 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### European Union

#### Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

##### SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration  $\geq 0.1\%$  (Regulation (EC) No. 1907/2006 (REACH), Article 59)

##### EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

# SAFETY DATA SHEET

OB1 PlumbersPal Hybrid Sealant & Adhesive White  
Date: 04.08.2023

Replaces: N/A  
Ref: 0520.0.BB/DL

Chemical name	CAS No	Restricted substance per REACH Annex XVII
Dioctyltin oxide	870-08-6	20.

## Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

## Export Notification requirements

This product contains substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals

Chemical name	European Export/Import Restrictions per (EC) 689/2008 - Annex Number
Dioctyltin oxide	I.1

## Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

## Persistent Organic Pollutants

Not applicable

## National regulations

### 15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

## SECTION 16: Other information

### Key or legend to abbreviations and acronyms used in the safety data sheet

#### Full text of H-Statements referred to under section 3

H226 - Flammable liquid and vapour  
H315 - Causes skin irritation  
H317 - May cause an allergic skin reaction  
H318 - Causes serious eye damage  
H332 - Harmful if inhaled  
H412 - Harmful to aquatic life with long lasting effects

#### Legend

TWA	TWA (time-weighted average)
STEL	STEL (Short Term Exposure Limit)
Ceiling	Ceiling Limit Value
*	Skin designation
SVHC	Substance(s) of Very High Concern
PBT	Persistent, Bioaccumulative, and Toxic (PBT) Chemicals
vPvB	Very Persistent and very Bioaccumulative (vPvB) Chemicals
STOT RE	Specific target organ toxicity - Repeated exposure
STOT SE	Specific target organ toxicity - Single exposure
EWC	European Waste Catalogue
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
IMDG	International Maritime Dangerous Goods (IMDG)
IATA	International Air Transport Association (IATA)
RID	Regulations concerning the International Transport of Dangerous Goods by Rail

# SAFETY DATA SHEET

OB1 PlumbersPal Hybrid Sealant & Adhesive White  
Date: 04.08.2023

Replaces: N/A  
Ref: 0520.0.BB/DL

---

## Key literature references and sources for data

No information available

**Prepared By** Product Safety & Regulatory Affairs

**Revision date** 05-Dec-2022

## Indication of changes

**Revision note** Not applicable.

**Training Advice** No information available

**Further information** No information available

## Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**